

Product code: FR2219

DUTARP Tarpaulins can be stitched and welded by high frequency welding machine with special Grommets / Eyelets & Reinforcements as per customer's requirement maximum size upto 60ft x 60ft (18mx18m)

Weight	420 Gsm
Thickness	0.35mm
Tensile Strength – Warp	52 Kgs / 3cm +/- 5%
Tensile Strength – Weft	43 Kgs / 3cm +/-5%
Tearing Strength – Warp	6 Kgs +/- 5%
Tearing Strength – Weft	4 Kgs +/-5%
Fire Retardancy	CPAI-84:1995;Section 6 Flammability Test for wall & Top Materials of Camping Tentage Products
Weathering Procedure	CPAI-84:1995 Section 4.2.2.3
Leaching Procedure	CPAI-84:1995 Section 4.1
Applications	Tarpaulins for Oil & Gas Store, Equipment Covers, Boat Covers, Tents
Colors Available	Orange, Grey, Red, Blue, Green, Yellow, White
Standard Roll Size	72" x 50Yds (1.8m x 45.7m)



Available in Ready Made Sizes:

20ft x 20ft (6mx6m)	30ft x 40ft (09mx12m)
30ft x 30ft (9mx9m)	40ft x 40ft (12mx12m)

