

WEBBING SLING BELT

SAFEMAX Webslings are manufactured from 100% Polyester Webbing. It is lightweight, durable and strong, flexible and easy to handle. Our Polyester Webslings with flat eye to eye loop ends are versatile slings for general use. Used in choker, basket or vertical hitches.

Safety Factor is 7:1

Suitable in temperature range of -40°C to 100°C.

Each sling is supplied with individual test certificate.

We customized various sizes in Three & Four Ply.

Color coded according to EN 1492-1 Standards



Flat Polyester Sling Type (Single Ply)

Webbing Width (in)	Color	WLL	Straight Lift I	Basket Lift U	7°-45° 	Choker Lift 	45°-60°
1	Violet	500	500	1000	700	400	500
2	Green	1000	1000	2000	1400	800	1000
3	Yellow	1500	1500	3000	2100	1200	1500
4	Grey	2000	2000	4000	2800	1600	2000
5	Red	2500	2500	5000	3500	2000	2500
6	Brown	3000	3000	6000	4200	2400	3000
8	Blue	4000	4000	8000	5600	3200	4000
10	Orange	5000	5000	10000	7000	4000	5000
12	Orange	6000	6000	12000	8400	4800	6000

***WLL in kg at different modes.

Flat Polyester Sling Type (Double Ply)

Webbing Width (in)	Color	WLL	Straight Lift I	Basket Lift U	7°-45° 	Choker Lift 	45°-60°
1	Violet	1000	1000	2000	1400	800	1000
2	Green	2000	2000	4000	2800	1600	2000
3	Yellow	3000	3000	6000	4200	2400	3000
4	Grey	4000	4000	8000	5600	3200	4000
5	Red	5000	5000	10000	7000	4000	5000
6	Brown	6000	6000	12000	8400	4800	6000
8	Blue	8000	8000	16000	11200	6400	8000
10	Orange	10000	10000	20000	14000	8000	10000
12	Orange	12000	12000	24000	16800	9600	12000

***WLL in kg at different modes.